



SEDIMENT LOG IN DITCH/CHANNEL SECTIONAL ELEVATION (NTS)




SECTION A-A (NTS)



TYPICAL OVERLAP

PLAN (NTS)

Overlap applies to situations where ditch/channel is wider than length of single Sediment Log.



NOTES

- 1. Sediment Logs shall be located as indicated in plans SWPPP or as directed by the Engineer.
- 2. Logs shall be selected, installed, and maintained with manufacturers' specifications and good engineering practices.

During Construction

SEDIMENT LOG AT STORM DRAIN SECTION-ELEVATION B-B (NTS)

- 3. Lay sediment log across prepared ditch or channel. Trenching or burial of Sediment Logs is not required. The intimate contact between the bottom of the Log and the ground is mandatory. The Logs shall be installed in the ditch, swale or channel bottom perpendicular to the flow of water as shown on detail this sheet.
- 4. Stake Log as shown. Stakes shall be placed through downstream side only as shown. DO NOT drive stakes through center of the log. Stakes must be driven into the ground as shown.
- 5. Ensure that no gaps exist between soil and bottom of Sediment Log. Repair any rills or undercuts promptly.
- 6. In rock conditions the Engineer will evaluate placement of Sediment Logs. 7. For ditch slopes that exceed 8%, install rock riprap for channel/ditch
- lining or rock check dams in place of Sediment Logs.
- 8. Remove Sediment Log and stakes once final stabilization requirements are met.

 Contractor to dispose of Sediment Logs and dispose of trapped sediment material and to fill shallow trench created by Sediment Log.

DETAIL **E1**

DESIGN DESIGN DRAWN CHECKED TEAM LEADER	ZITAO FANG	2-2006 2-2006	ARIZONA DEPARTMENT OF TRANSPORTATION INTERMODAL TRANSPORTATION DIVISION ROADSIDE DEVELOPMENT SECTION EROSION/SEDIMENT CONTROL AND WATER QUALITY PROTECTION DETAIL		
10072		COOKTION		SHEET	OF
TRACS NO.					0F

s:\rdwyeng\users\a3956\ 05:57:28 PM 02/27/2006 S:\RdwyEng\RdsdDev\BMPs\Sediment_Log.dgi